

Fire Ribbon Direct Vent Slim 26" with mandatory safety screen

Model No.

26

Viewing Area
Exterior Dimension
Framing Dimension
Gas Type*
Gas Connection
On/Off
Efficiency
Venting Options
Vent Type

26.19" W x 14.5" H
38.75" W x 27.25" H x 7.61" D
Mounts flush on wall
Natural or LP/Propane
1/2" pipe
Programmable/thermostatic remote control
Up to 80%
Through exterior wall or vertical through roof.
DuraVent DirectVent Pro 46DVA
Unit supplied with starter collar & wall
pass through

Fan
Electric
BTU input Natural gas
LP/propane
Doors/glass
Interior Color
Sustained operating gas pressure
parameters:

n/a
n/a
11,000 - 19,000 BTU/h
11,000 - 19,000 BTU/h
Fixed ceramic glass panel
Reflective Porcelain enamel firebox liner
Natural gas 5.5" - 10.5" w.c.
LP/propane 11.0" - 13.0" w.c.

Certifications

Omni-Test Laboratories Z21.88a-2007
CSA 2.33a-2007 CAN/CGA-2.17-M91

Options

*Must be specified at time
of ordering.

Surround options are satin black or
stainless steel
Media options: comes with Ebonyglass
Iceglass optional

