

Fire Ribbon Vent Free Slim 26" with mandatory safety screen

Model No.

26

Viewing Area
Exterior Dimension
Clearance to combustibles

26.19" W x 14.5" H
38.75" W x 27.25" H x 7.61" D
Rear: 0", Left Side: 6", Right Side: 6",
Ceiling: 12", Floor 3"

Gas Type*
Gas Connection
On/Off
Efficiency
Venting Options
Vent Type
Fan
Electric
BTU input Natural gas
LP/propane

Natural or LP/Propane
3/8" pipe
Programmable/thermostatic remote control
Up to 95%
None
None
None

Doors/glass
Interior Color

11,000 - 19,000 BTU/h
11,000 - 19,000 BTU/h
None
Black reflective Porcelain enamel
firebox liner
Satin black or brushed stainless steel
Natural gas 5.5" - 10.0" w.c.
LP/propane 11.0" - 13.0" w.c.
Omni-Test Laboratories
ANSI Z21.11.2-2013

Surround Options
Sustained operating gas pressure
parameters:
Certifications

Options
*Must be specified at time
of ordering.

Surround options are satin black or
stainless steel
Media options: comes with Ebonyglass
Iceglass optional

Restrictions:

Vent-free fireplaces are prohibited in certain
geographies. Please check local codes. Canada,
CA and NYC prohibit vent-free fireplaces. Vent-free
fireplaces are also prohibited for use in bedrooms,
bathrooms and above 4,500 ft elevation.

