

## Fire Ribbon Direct Vent Slim 46" with mandatory safety screen

### Model No.

**46**

Viewing Area  
Exterior Dimension  
Framing Dimension  
Gas Type\*  
Gas Connection  
On/Off  
Efficiency  
Venting Options  
Vent Type

46" W x 12" H  
58.40" W x 25.25" H x 8" D  
Mounts flush on wall  
Natural or LP/Propane  
1/2" pipe  
Programmable/thermostatic remote control  
Up to 80%  
Through exterior wall or vertical through roof.  
Duravent DirectVent Pro 58DVA  
Unit supplied with starter collar & wall  
pass through

Fan  
Electric  
BTU input Natural gas  
LP/propane

n/a  
n/a  
19,000 - 29,000 BTU/h  
19,000 - 29,000 BTU/h

Doors/glass  
Interior Color  
Sustained operating gas pressure  
parameters:

Fixed ceramic glass panel  
Reflective Porcelain enamel firebox liner  
Natural gas 5.5" - 10.5" w.c.  
LP/propane 11.0" - 13.0" w.c.

### Certifications

Omni-Test Laboratories ANSI Z21.88a-2007  
CSA 2.33a-2007 CAN/CGA-2.17-M9

### Options

\*Must be specified at time of ordering.

Surround options are satin black or  
stainless steel  
Media options: comes with Ebonyglass  
Iceglass optional

