

## Fire Ribbon Direct Vent 4 ft VU Thru with mandatory safety screen

### Model No.

**49**

### Viewing Area

48.33" W x 17" H

### Exterior Dimension

53.75" W x 32" H x 20.5" D

### Framing Dimension

64.50" W x 40" H x 22" D

### Gas Type\*

Natural or LP/Propane

### Gas Connection

1/2" pipe

### On/Off

Programmable / thermostatic remote control standard

### Efficiency

Up to 80%

### Venting Options

Through exterior wall or vertical through roof.

**Must Vent 2' vertically before any horizontal venting**

### Vent Type

DuraVent DirectVent Pro 46DVA

**Must source locally, not included.**

Thermostat activated 160 c.f.m.

110 V.

### Fan

Electric

BTU input Natural gas

26,000 - 37,500 BTU/h

BTU input LP/propane

27,000 - 37,000 BTU/h

Doors/glass

2 Fixed ceramic glass panels

Interior Color

Satin Black

Sustained operating gas pressure parameters

Natural gas 4.5" - 10.5" w.c.

LP/propane 11.0" - 13.0" w.c.

Certifications

Omni-Test Laboratories ANSI Z21.88-2014  
CSA 2.33-2014, "Standard for Vented Gas  
Fireplace Heaters." CAN/CGA 2.17-M91  
(R2009), "Gas-Fired Appliances for Use at  
High Altitudes." CAN/CSA P.4.1-09 (R2014),  
"Testing Method for Measuring Annual  
Fireplace Efficiency."

### Options

\*Must be specified at time of ordering.

### Note:

This is a high throughput gas appliance and critical attention is needed to size the gas pipes properly.

### Fire Objects

Media Tray, required when using fire objects

