

Fire Ribbon Direct Vent 6 ft

MODEL NO.

Viewing Area	72.25" W x 15" H
Exterior Dimension	82.25" W x 32.19" H x 23.75" D
Framing Dimension	82.25" W x 38" H x 24.75" D
Gas Type*	Natural or LP/Propane
Gas Connection	1/2" pipe
On/Off	Programmable/thermostatic remote control standard
Efficiency	Up to 80%
Venting Options	Through exterior wall or vertical through roof, Must vent 3' vertically before horizontal venting.
Vent Type	DuraVent DirectVent Pro 58DVA Must source locally, not included.
Fan	Controlled with hand held remote
Electric	110 V.
BTU input Natural gas	40,000 - 64,500 BTU/h
BTU input LP/propane	37,000 - 64,500 BTU/h
Doors/glass	Fixed ceramic glass panel
Interior Color	Satin Black
Sustained operating gas pressure parameters:	4.5" - 10.5" w.c. for Natural gas 11.0" - 13.0" w.c. for LP/propane
Certifications	Omni-Test Laboratories ANSI Z21.88-2014, CSA 2.33-2014 CGA 2.17 - M91 (R2009), CSA P.4.1 - 09 (R2014)
Options	Fire Objects
*Must be specified at time of ordering.	Media Tray, required when using fire objects
	Power Venting
	Heat Redistribution Kit

Note: This is a high throughput gas appliance and critical attention is needed to size the gas pipes properly.

19E with mandatory safety screen

