

Fire Ribbon Direct Vent 5 ft

MODEL NO.

Viewing Area

Exterior Dimension

Framing Dimension

Gas Type*

Gas Connection

On/Off

Efficiency

Venting Options

Vent Type

Fan

Electric

BTU input Natural gas

BTU input LP/propane

Doors/glass

Interior Color

Sustained operating gas pressure parameters:

Certifications

Options

*Must be specified at time of ordering.

Note: This is a high throughput gas appliance and critical attention is needed to size the gas pipes properly.

60E with mandatory safety screen

60" W x 14.75" H

69.25" W x 29" H x 23.25" D

72.25" W x 36.25" H x 24.75" D

Natural or LP/Propane

1/2" pipe

Programmable / thermostatic remote control standard

Up to 78%

Through exterior wall or vertical through roof,

Must vent 3' vertically before horizontal venting.

DuraVent DirectVent Pro 58DVA Must source locally, not included.

Thermostat activated 160 c.f.m.

110 V

35,000 - 52,000 BTU/h

42,000 - 52,000 BTU/h

Fixed ceramic glass panel

Satin Black

4.5" - 10.5" w.c. for Natural gas

11.0" - 13.0" w.c. for LP/propane

Omni-Test Laboratories ANSI Z21.88-2014/CSA

2.33-2014, CGA 2.17-M91 (R2009),

CSA P.4.1-09 STANDARDS

Fire Objects

Media Tray, required when using fire objects

