

Fire Ribbon Direct Vent 6 ft

MODEL NO.

Viewing Area

Exterior Dimension

Framing Dimension

Gas Type*

Gas Connection

On/Off

Efficiency

Venting Options

Vent Type

Fan

Electric

BTU input Natural gas

BTU input LP/propane

Doors/glass

Interior Color

Sustained operating gas pressure parameters:

Certifications

Options

*Must be specified at time of ordering.

Note: This is a high throughput gas appliance and critical attention is needed to size the gas pipes properly.

19E with mandatory safety screen

72.25" W x 15" H

82.25" W x 32.19" H x 23.75" D

82.25" W x 38" H x 24.75" D

Natural or LP/Propane

1/2" pipe

Programmable/thermostatic remote control standard

Up to 80%

Through exterior wall or vertical through roof,
Must vent 3' vertically before horizontal venting.

DuraVent DirectVent Pro 58DVA

Must source locally, not included.

Controlled with hand held remote

110 V.

40,000 - 64,500 BTU/h

37,000 - 64,500 BTU/h

Fixed ceramic glass panel

Satin Black

4.5" - 10.5" w.c. for Natural gas

11.0" - 13.0" w.c. for LP/propane

Omni-Test Laboratories ANSI Z21.88-2014,

CSA 2.33-2014

CGA 2.17 - M91 (R2009),

CSA P.4.1 - 09 (R2014)

Fire Objects

Media Tray, required when using fire objects

