

Fire Ribbon Direct Vent 3 ft with mandatory safety screen

Model No.

Viewing Area
Exterior Dimension
Framing Dimension
Gas Type*
Gas Connection
On/Off

Efficiency
Venting Options

Vent Type

Fan
Electric
BTU input Natural gas
BTU input LP/propane
Doors/glass
Interior Color
Sustained operating gas
pressure parameters:

Certifications

Options

*Must be specified at time of ordering.

87

Does not require vertical venting

36" W x 16" H
45" W x 32" H x 22.5" D
46" W x 36.25" H x 23" D
Natural or LP/Propane*
1/2" pipe
Programmable /thermostatic remote
control standard
Up to 80%
Through exterior wall or vertical
through roof. **At order please specify
if venting vertically or horizontally.**
DuraVent DirectVent Pro 46DVA
Must source locally, not included.
Thermostat activated 160 c.f.m.
110 V
19,000 - 28,000 BTU/h
19,000 - 28,000 BTU/h
Fixed ceramic glass panel
Satin Black
Natural gas 4.5" - 10.5" w.c.
LP/propane 11.0" - 13.0" w.c.

Omni-Test Laboratories
ANSI Z21.88.2009
CSA 2.33-2009

Fire Objects and Media Tray*
*required when using fire objects

88

Requires 3' vertical vent before any horizontal venting

36" W x 16" H
45" W x 32" H x 22.5" D
46" W x 36.25" H x 23" D
Natural or LP/Propane*
1/2" pipe
Programmable / thermostatic remote
control standard
Up to 80%
Through exterior wall or vertical through roof.
**Requires 3' vertical venting from the collar
before any horizontal venting.**
DuraVent DirectVent Pro 46DVA
Must source locally, not included.
Thermostat activated 160 c.f.m.
110 V
25,000 - 35,000 BTU/h
25,000 - 35,000 BTU/h
Fixed ceramic glass panel
Satin Black
Natural gas 4.5" - 10.5" w.c.
LP/propane 11.0" - 13.0" w.c.

Omni-Test Laboratories
ANSI Z21.88.2009
CSA 2.33-2009

Fire Objects and Media Tray*
*required when using fire objects

