





SPARK MODERN FIRES
 99 B GREENWOOD AVENUE
 BETHEL, CT 06801
 TOLL FREE: 1-866-938-3846
 www.sparkfires.com



RIGHT SIDE VIEW



FRONT VIEW

MUST VERTICALLY VENT 3' FIRST
 BEFORE ANY HORIZONTAL VENTING

SPECIFICATIONS

- GLASS VIEWING AREA: 72.25"W X 16"H
- OUTER DIMENSIONS: 81.25"W X 39"H X 22.5"D
- *GAS TYPE: NATURAL OR LP/PROPANE
- *ON/OFF: REMOTE CONTROL
- EFFICIENCY: UP TO 80%
- VENTING OPTIONS: THROUGH ROOF OR EXTERIOR WALL
- **VENT TYPE: 2 SIMPSON DURAVENT PRO GS 6 5/8" DIAMETER
 MUST SOURCE LOCALLY, NOT INCLUDED
- FAN: THERMOSTAT ACTIVATED 160 C.F.M.
- ELECTRIC: 110 V.
- BTU INPUT: 52,000—77,000 (75,000LP)BTU/H
- DOORS/GLASS: FIXED CERAMIC GLASS PANEL
- INTERIOR COLOR: SATIN BLACK
- CERTIFICATION: OMNI-TEST LABORATORIES
 ANSI Z21.88-2009 CSA 2.33-2009


OPTIONS: SAFETY SCREEN*

*MUST BE SPECIFIED AT TIME OF ORDERING. (SAFETY SCREEN IS RECOMMENDED FOR PUBLIC INSTALLATIONS)

**MUST SOURCE LOCALLY. FIRE OBJECTS AND MEDIA TRAY*
 (TRAY REQUIRED WHEN USING FIRE OBJECTS)

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 1847-007.



DIRECT VENT FIREPLACES

FIRE RIBBON DIRECT VENT 6" FIREPLACE (MODEL 19)