

Fire Ribbon Direct Vent Slim 46" Vent Free and Direct Vent** with mandatory safety screen Front View

Model No.	46
Viewing Area	46" W x 12" H
Exterior Dimension	58.40" W x 25.25" H x 8" D
Framing Dimension	Mounts flush on wall
Gas Type*	Natural or LP/Propane
Gas Connection	1/2" pipe
On/Off	Programmable/thermostatic remote control standard with manual control panel on unit
Efficiency	Up to 80% for Direct Vent Up to 95% for Vent Free
Direct Venting Options**	Through exterior wall or vertical through roof.
Vent Type**	DuraVent DirectVent Pro 58DVA. Unit supplied with starter collar & wall pass through
Fan	n/a
Electric	n/a
Direct Vent BTU input**	19,000 - 29,000 BTU/h for natural gas 19,000 - 29,000 BTU/h for LP/Propane
Vent Free BTU input	23,000—37,000 BTU/h for natural gas 25,000—37,000 BTU/h for LP/Propane
Doors/glass	Fixed ceramic glass panel
Interior Color	Reflective Porcelain enamel firebox liner
Max Supply Pressure	10.0" w.c. for natural gas 13.0" w.c. for LP/Propane
Min Supply Pressure	5.5" w.c. for natural gas 11.0" w.c. for LP/Propane
Direct Vent Certifications	Omni-Test Laboratories ANSI Z21.88a-2007 CSA 2.33a-2007 CAN/CGA-2.17-M9
Vent Free Certifications	Omni-Test Laboratories ANSI Z21.11.2-2013
Options	Surround options are satin black or stainless steel
	Media options are Ebony or Ice glass

*Must be specified at time of ordering.

