

**Direct Vent 6FT
6FT Montana**

MODEL NO.

19W with mandatory safety screen

Viewing Area
Exterior Dimension
Framing Dimension
Gas Type*
Gas Connection
On/Off
Efficiency
Venting Options

72.75" W x 16" H
81." W x 38.25" H x 23.75" D
82" W x 39.5" H x 23.5" D
Natural or LP/Propane
1/2" pipe
Programmable/thermostatic remote control standard
Up to 78% (Flue loss Calculation)
Through exterior wall or vertical through roof.

Must vent 3' vertically before horizontal venting.

DuraVent DirectVent Pro 58DVA
Must source locally, not included.
Controlled with hand held remote
110 V.

Vent Type

Fan
Electric
BTU input Natural gas
BTU input LP/propane
Doors/glass
Interior Color*
Sustained operating gas pressure
parameters:

48,000 - 58,000 BTU/h
46,000 - 57,000 BTU/h
Ceramic glass panels
Enamelled black reflective side and rear panels
5.0" - 10.5" w.c. for Natural gas
11.0" - 13.0" w.c. for LP/propane
Omni-Test Laboratories
ANSI Z21.88 / CSA2.33-2019
Standard for Vented Gas Fireplace Heaters

Certifications

Fire Objects
Realistic hand made stone set
Log set available at no extra charge

Options

*Must be specified at time of ordering.

